

*FR 5019
Downstream
Optical Receiver*



The FR 5019 is a 19" rack mount downstream 1310 /1550 nm receiver.

Features:

- 1U 19 inch rack housing
- 45 to 870 forward bandwidth
- AGC / MGC (automatic/ manual) gain control mode
- +1 dB to -3 dB adjustable slope range
- Front panel LCD display
- Microprocessor control & monitoring
- Redundancy A/B switch receiver
- RS 485 control interface

Specifications

ACI Communications, Inc.				FR5019 Downstream Optical Receiver
Optical Parameters				
PARAMETERS	CONDITIONS	UNIT	SPECIFICATIONS	
Wavelength		nm	1310 / 1550 ±20	
Optical module			2 with AB switch	
Input power		dBm	+3 to -10	
Connector type			SC / APC; FC / APC	
Detector			In GaAs PIN	
RF Parameters				
Frequency response		MHz	48 to 870	
Output level		dBmV /Ch	36 (3 dBm input, OMI = 3.6%)	
Flatness		dB	≤1.5 peak to valley	
Control interface			RS 485	
RF test point		-dB	20	
Input impedance		Ω	75	
Return loss	min.	dB	16	
Power				
Power supply		VAC, Hz	90 to 260, 50 / 60	
AC power consumption	max.	W	30	
Environmental				
Operating Temperature		°C	0 to 50	
Storage temperature		°C	-20 to +70	
Relative humidity	max.	%	85	
Physical				
Dimension	d x w x h	mm	350 x 485 x 45	
Weight		Kg	<4.2	

Confidential

Information contained in this document is subject to change without notice.

Revision date: 01/02/2009

Ordering Information:

F R 5 0 1 9

- [] []

CONNECTOR

F C = FC/APC

S C = SC/APC

ACI Communications, Inc.
23307 - 66th Avenue South - Kent, WA - 98032
Phone: (253) 854-9802 - Fax: (253) 813-1001 - www.acicomms.com



ACI Communications, Inc. reserves the right to discontinue the manufacture or change specifications without prior notice on any parts illustrated in this data sheet. Current drawings are available upon request.

Rev F 9-3-2010 **ACI Communications, Inc.**
Printed in U.S.A.